

PowerGlow

Maximum Brightness
Superior Life

Ideal for commercial spaces



Hospitality



Retail



Offices

PowerGlow : Maximum Brightness & Superior Life

- **Specially designed for commercially spaces** – High efficacy with long life
- Maximum Brightness of **120 Lm/Watt**
- Superior **35000 Hrs life**
- Trendy and stylish – **Ultra thin trim** (only 4mm) to blend well with the ceiling
- **Deep recessed light source** for low glare
- Available in 2 sizes : 144mm cutout and 164 mm cutout
- Super robust construction
 - Wide voltage protection from 160V – 360V and **surge protection of 3KV**
- Premium aluminum heatsink for better heat management and long life
- No harmful UV radiation



PowerGlow 8.5W – 1020 Lm



General Specs

Application	Downlighter
Color & Material	White; Plastic + Aluminum
Lamp base & wattage (Color Temperature)	LED 8.5W, 240V 50Hz 3000K, 4000K, 6500K
Dimensions (L X W X H)mm	152 mm (W) x 44 mm (H)
Cut out	144 mm
Lumen Output	1020 Lm
Master Pack	8

Power Glow 8.5W - 1020 Lm

Essential

35000 Hrs Life

Bright light with 120 Lm/watt

Wide voltage protection (160-360V),
Surge protection of 3kV

Premium aluminum die cast heatsink



PowerGlow 10W – 1200 Lm



General Specs

Application	Downlighter
Color & Material	White; Plastic + Aluminum
Lamp base & wattage (Color Temperature)	LED 10W, 240V 50Hz 3000K, 4000K, 6500K
Dimensions (L X W X H)mm	152 mm (W) x 44 mm (H)
Cut out	144 mm
Lumen Output	1200 Lm
Master Pack	8

Power Glow 10W - 1200 Lm

Essential

35000 Hrs Life

Bright light with 120 Lm/watt

Wide voltage protection (160-360V),
Surge protection of 3kV

Premium aluminum die cast heatsink



PowerGlow 13.5W – 1600 Lm



General Specs

Application	Downlighter
Color & Material	White; Plastic + Aluminum
Lamp base & wattage (Color Temperature)	LED 10W, 240V 50Hz 3000K,4000K, 6500K
Dimensions (L X W X H)mm	174 mm (W) x 52 mm (H)
Cut out	164 mm
Lumen Output	1620 Lm
Master Pack	8

Power Glow 13.5W - 1600 Lm

Essential

35000 Hrs Life

Bright light with 120 Lm/watt

Wide voltage protection (160-360V),
Surge protection of 3kV

Premium aluminum die cast heatsink



PowerGlow 16.5W – 1980 Lm



General Specs

Application	Downlighter
Color & Material	White; Plastic + Aluminum
Lamp base & wattage (Color Temperature)	LED 16.5W, 240V 50Hz 3000K, 4000K, 6500K
Dimensions (L X W X H)mm	174 mm (W) x 52 mm (H)
Cut out	164 mm
Lumen Output	1980 Lm
Master Pack	8

Power Glow 16.5W – 1980lm

Essential

35000 Hrs Life

Bright light with 120 Lm/watt

Wide voltage protection (160-360V),
Surge protection of 3kV

Premium aluminum die cast heatsink



Commercials

12NC	Description	MRP
929001951868	PowerGlow 8.5W 1000 Lm LED DL (WW)	1400
929001951869	PowerGlow 8.5W 1000 Lm LED DL (NW)	1400
929001951870	PowerGlow 8.5W 1000 Lm LED DL (CDL)	1400
929001951871	PowerGlow 10W 1200 Lm LED DL (WW)	1500
929001951872	PowerGlow 10W 1200 Lm LED DL (NW)	1500
929001951873	PowerGlow 10W 1200 Lm LED DL (CDL)	1500
929001951874	PowerGlow 13.5W 1600 Lm LED DL (WW)	1700
929001951875	PowerGlow 13.5W 1600 Lm LED DL (NW)	1700
929001951876	PowerGlow 13.5W 1600 Lm LED DL (CDL)	1700
929001951877	PowerGlow 16W 2000 Lm LED DL (WW)	2000
929001951878	PowerGlow 16W 2000 Lm LED DL (NW)	2000
929001951879	PowerGlow 16W 2000 Lm LED DL (CDL)	2000

