
Crompton

Crompton Greaves Consumer Electricals Limited Tower 3, 1st Floor, East Wing, Equinox Business Park, LBS Marg, Kurla (West), Mumbai-400070



REV 00 DATE: 13/07/2018 SHEET 1 # 2 DOCUMENT No. D / PD - 05



DIMENSIONS SHOWN ARE FOR INSTALLATION REFERENCES ONLY AND WILL BE VARYING ACCORDING TO THE MFG. PROCESSES.

GENERAL

This decorative luminaire designed for LED tube comprises of CRCA pre coated housing and cover with plastic end cap. This luminaire is recommended for wall / ceiling mounting purpose in domestic interiors, general indoor area like staircase and corridors.

CAT. REF.	LAMP	VOLTAGE (V)	** MAINS CURRENT (A)	*APPROX WT(Kg)
IGP162 LT8-16	2 x T8 LED LAMP	240	0.180 (for 2 x 20W)	0.800

* ONLY FOR STRUCTURAL/MOUNTING DESIGN CONSIDERATION.
** RATED SYSYTEM WATTAGE AND CURRENT WILL HAVE TOLERANCE AS PER IS 15885

Title	Type IGP16 for LED TUBE	CUSTOMER REFERENCE:
General Purpose Luminaire	AMD No. :	
For LED TUBE	ALL DIMENSIONS ARE IN MM	
AS EFFORTS ARE ON CONSTANTLY TO IMPROVE THE DESIGN AND METHODS OF MANUFACTURE OF THE PRODUCT, THE PRODUCT SUPPLED MAY DIFFER IN DETAIL FROM THE DATA GIVEN HERE IN.	THIS DRAWING & DESIGN IS THE PROPERTY OF CROMPTON GREAVES CONSUMER ELECTRICALS LTD. AND MUST NOT BE COPIED OR LENT WITHOUT THEIR PERMISSION IN WRITING.	DRG NO. TD 0907124

Crompton

Crompton Greaves Consumer Electricals Limited Tower 3, 1st Floor, East Wing, Equinox Business Park, LBS Marg, Kurla (West), Mumbai-400070



SHEET 2 # 2 DOCUMENT No. D / PD - 05 REV 00 DATE: 13/07/2018

MATERIAL SPECIFICATION

Housing
 CRCA, Pre coated in white shade from out side and inside light grey
 Cover
 CRCA, Pre coated in white shade from out side and inside light grey

3. End cap PC end cap white, Blue deco cap with push fit holder for twin T8 and pop up

for single T8.

4. Internal wiring PVC insulated single strand copper wire0.5 sq.mm.

5. Mains Terminal 2way 5amps suitable for terminating 1.5sq. mm incoming cable.

6. Hardware MS zinc plated and passivated.

ACCESSORIES

Cat ref Lamp Holder LED lamp IGP162LT8-16 G5-13 2No. T8 LED lamp

INSTALLATION

Cable Entry : Through conduit suspension pipe.

Mounting System : 2No. Ø20 knockout and 2no. Ø6.5mm mounting.
 Maintenance : The cover can be remove for mains connection.

4. Protection : IP20

ORDERING REFERENCE

IGP162LT8-16


SPARES ORDERING REFERENCE

Cat Ref. Lamp Holder


IGP162LT8-16 LH47

WIRING DIAGRAM

IGP161LT8-16



IGP162LT8-16



AS EFFORTS ARE ON CONSTANTLY TO IMPROVE THE DESIGN AND METHODS OF MANUFACTURE OF THE PRODUCT, THE PRODUCT SUPPLED MAY DIFFER IN DETAIL FROM THE DATA GIVEN HERE IN.

THIS DRAWING & DESIGN IS THE PROPERTY OF CROMPTON GREAVES CONSUMER ELECTRICAL SLTD. AND MUST NOT BE COPIED OR LENT WITHOUT THEIR PERMISSION IN WRITING.

DRG NO.

TD 0907124