



DIMENSIONS SHOWN ARE FOR INSTALLATION REFERENCES ONLY AND WILL BE VARYING ACCORDING TO THE MFG. PROCESSES.

GENERAL

This integrated LED Bulk Head luminaire comprises of Plastic housing,diffuser . This is recommended to be used in comercial outdoor,corridors,parking light application.

CAT. REF.	SYSTEM WATTAGE	VOLTAGE (V)	MAINS CURRENT(A)	*APPROX. WT(Kg)
LBHP-10-CDL	10 W	240	0.042	0.29

ONLY FOR STRUCTURAL/MOUNTING DESIGN CONSIDERATION.
 RATED SYSTEM WATTAGE AND CURRENT WILL HAVE TOLERANCE $\pm 10\%$

Title LED Bulkhead Luminaire	Type LBHP-10-CDL	CUSTOMER REFERENCE :
	AMD No. : ALL DIMENSIONS ARE IN MM	
AS EFFORTS ARE ON CONSTANTLY TO IMPROVE THE DESIGN AND METHODS OF MANUFACTURE OF THE PRODUCT, THE PRODUCT SUPPLIED MAY DIFFER IN DETAIL FROM THE DATA GIVEN HERE IN.	THIS DRAWING & DESIGN IS THE PROPERTY OF CROMPTON . AND MUST NOT BE COPIED OR LENT WITHOUT THEIR PERMISSION IN WRITING.	DRG NO. TD 0907106

MATERIAL SPECIFICATION

- | | |
|--------------------|---|
| 1. Housing | ABS Plastic. |
| 2. Cover | PC Diffused. |
| 3. Internal Wiring | PVC insulated multistrand strand copper wire. Teflon coated wire for LED. |

ELECTRICAL PARAMETERS

Rated Voltage (V)	:	240
Frequency (Hz)	:	50
Operating Voltage Range(V)	:	140 - 270~
Current (A) @ 240V	:	0.042
Wattage (W) @ 240V	:	10
PF	:	≅ 0.90

INSTALLATION

- | | |
|--------------------|--|
| 2. Mounting System | 2Nos Ø4 Holes provided on housing for mounting purpose. |
| 3. Maintenance | Cover of Housing can be removed for accessories maintenance. |
| 4. Protection | IP 65 |

SPARES ORDERING REFERENCE

Cat. Ref.
LBHP-10-CDL

ORDERING REFERENCE

Cat. Ref.
LBHP-10-CDL

AS EFFORTS ARE ON CONSTANTLY TO IMPROVE THE DESIGN AND METHODS OF MANUFACTURE OF THE PRODUCT, THE PRODUCT SUPPLIED MAY DIFFER IN DETAIL FROM THE DATA GIVEN HERE IN.

THIS DRAWING & DESIGN IS THE PROPERTY OF CROMPTON . AND MUST NOT BE COPIED OR LENT WITHOUT THEIR PERMISSION IN WRITING.

DRG NO.

TD 0907106