



Smart **Brite**

36w 4000lumens **Metal Batten**

BN021 40s

Positioning

- **High Brightness 36w 4000lm batten for commercial applications**
- Designed for parking spaces, go-downs and corridors/large spaces
- Delivers **110 lumen/watt** efficiency

Key Specs

- **36w 4000lm aluminium batten**
- Length – 4 feet
- CRI > 80 for accurate colour rendering
- Robust **metal** construction for better heat dissipation and longer life
- **Eye Comfort Technology** with no blue light hazard
- CCT: 6500k (CDL), 4000k (NW)

Product Image



Diffuser:

Serrated Diffuser for wider light spread and better eye comfort

Construction:

Robust Aluminium channel for better heat dissipation & long life

User Safety:

Dedicated earthing provision and cable included in box for user safety

Product Packaging

Product USP:
Best In Class LEDs. 110lm/watt efficiency



Product Tagline:
Superior LEDs. Lasting Performance

Focus on Application Areas:
Godowns. Parking Spaces

Specifications

Lumen Output	4000 Lm
System Wattage	36 W
Efficacy	>110lm/watt
CCT	6500K & 4000k
CRI	>80
Life Class	20,000 hrs @ 35`C ambient temperature
Mounting	Wall/Surface
Housing	Aluminum Extrusion
IP	IP 20
Luminaire compliance	Relevant LED IS standards
Operating temperature	Up to 35 deg C
PF	> 0.9
THD	< 30 %
Input voltage range	160V - 240V AC
diffuser	PC
Dimensions	1185mm X 22mm X 36mm (approx.)
Serviceability	Non Replaceable Driver

Signify