



CROSSBOW UFO

HIGHBAY LIGHT

PRODUCT INFORMATION

Light Source	CREE
Color Temperature	3000K/4000K/6500K
Efficacy	120-140 lm/W

ELECTRICAL DATA

Power Supply	Hansa Green
Input Voltage	AC 100-265V
Input Frequency	50-60 Hz
Power Factor	>0.9
Efficiency	>90%
THD	<15%

GENERAL

Housing & Optics	Aluminum Die-cast & Tempered Glass
Ambient Temperature	-25°C to 50°C
Storage Temperature	-40°C to 50°C
Humidity	RH10% - 90%
Safety Features	Open Circuit, Short Circuit & Over Voltage Protection
IP Rating	IP66

LED Life Time:

>50,000 h

Type:



Indoor/Outdoor

Body Color:

Black

Warranty:

2 years limited warranty



*Dimensions are given in the table below . All measurements are in mm

Model No.	Power (W)	Lumens	CCT	CRI	Beam Angle	Dimension
HBL-UFO-G-100	100	13000±10% lm	3000K/4000K/6500K	>80	100°	D:290∅, H:150
HBL-UFO-G-150	150	20000±10%lm	3000K/4000K/6500K	>80	100°	D:330∅, H:160
HBL-UFO-G-200	200	26000±10%lm	3000K/4000K/6500K	>80	100°	D:450∅, H:170

Ordering Code

Power (W)	CCT : 3000K	CCT : 4000K	CCT : 6500K
100	HBL-UFO-G-100-K30	HBL-UFO-G-100-K40	HBL-UFO-G-100-K65
150	HBL-UFO-G-150-K30	HBL-UFO-G-150-K40	HBL-UFO-G-150-K65
200	HBL-UFO-G-200-K30	HBL-UFO-G-200-K40	HBL-UFO-G-200-K65

